

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A ~~computer-implemented~~ method of discovering a network path that satisfies a quality of service (QoS) requirement, the method comprising the ~~computer-implemented steps of:~~
receiving, at a first router, a first data packet that indicates a destination and said QoS requirement;
updating said first data packet to indicate an identity of said first router;
determining whether a least-delay path from said first router to said destination satisfies said QoS requirement;
determining whether said first data packet has visited any router in said least-delay path other than said first router;
if said least-delay path satisfies said QoS requirement and said first data packet has not visited any router in said least-delay path other than said first router, then sending said first data packet to a second router in said least-delay path; and
receiving, at said first router, a second data packet that indicates a path taken by said first data packet to said destination.
2. (Original) The method of Claim 1, wherein said first router has links, and further comprising:
if said least-delay path does not satisfy said QoS requirement, then performing steps comprising:
determining one or more of said first router's links that satisfy said QoS requirement;
and
sending a copy of said first data packet through said one or more of said first router's links that satisfy said QoS requirement.
3. (Original) The method of Claim 1, wherein said first router has links, and further comprising:
if said first data packet has visited a router in said least-delay path other than said first router, then performing steps comprising:

determining one or more of said first router's links that satisfy said QoS requirement;
and
sending a copy of said first data packet through said one or more of said first router's
links that satisfy said QoS requirement.

4. (Original) The method of Claim 1, further comprising:
in response to receiving said first data packet, updating a table to indicate that said
first router has received a copy of said first data packet.
5. (Currently Amended) A computer-implemented method of discovering a network
path that satisfies a quality of service (QoS) requirement, the method comprising ~~the
computer-implemented steps of:~~
receiving, at a first router, a data packet that indicates a destination and said QoS
requirement;
determining whether said data packet indicates that a path to said destination has
been found;
determining whether a least-delay path from said first router to said destination
satisfies said QoS requirement;
if said data packet indicates that a path to said destination has been found, and if said
least-delay path from said first router to said destination does not satisfy said
QoS requirement, then eliminating said data packet; and
if said data packet does not indicate that a path to said destination has been found,
and if said least-delay path from said first router to said destination satisfies
said QoS requirement, then performing steps comprising:
updating said data packet to indicate that a path to said destination has been
found; and
sending said data packet through said link that leads to said second router on
said least-delay path.
6. (Currently Amended) A computer-implemented method of discovering a network
path that satisfies a quality of service (QoS) requirement, the method comprising ~~the
computer-implemented steps of:~~

receiving, at a first router that has links, a data packet that indicates a destination and said QoS requirement;

determining whether said first router previously has received a copy of said data packet;

if said first router previously has received a copy of said data packet, then eliminating said data packet; and

if said first router previously has not received a copy of said data packet, then performing steps comprising:

updating a table to indicate that said first router has received a copy of said data packet;

determining whether said data packet indicates that a path to said destination has been found;

determining whether a least-delay path from said first router to said destination satisfies said QoS requirement;

if said data packet indicates that a path to said destination has been found, then performing steps comprising:

if said least-delay path from said first router to said destination does not satisfy said QoS requirement, then eliminating said data packet; and

if said least-delay path from said first router to said destination satisfies said QoS requirement, then sending said data packet through a link that leads to a second router on said least-delay path; and

if said data packet does not indicate that a path to said destination has been found, then performing steps comprising:

determining one or more of said first router's links that satisfy said QoS requirement;

if said least-delay path from said first router to said destination does not satisfy said QoS requirement, then sending a copy of said data packet through said one or more of said first router's links that satisfy said QoS requirement; and

if said least-delay path from said first router to said destination satisfies said QoS requirement, then performing steps comprising:
determining whether said data packet has visited any router in said least-delay path other than said first router;
if said data packet has visited a router in said least-delay path other than said first router, then sending a copy of said data packet through said one or more of said first router's links that satisfy said QoS requirement; and
if said data packet has not visited any router in said least-delay path other than said first router, then performing steps comprising:
updating said data packet to indicate that a path to said destination has been found; and
sending said data packet through said link that leads to said second router on said least-delay path.

7. (Currently Amended) A ~~computer-implemented~~ method of discovering a least-cost network path, the method comprising ~~the computer-implemented steps of:~~
receiving, at a first router, a first data packet that indicates a destination;
updating said first data packet to indicate an identity of said first router;
determining whether said first data packet has visited any router in a least-cost path from said first router to said destination, not including said first router;
if said first data packet has not visited any router in said least-cost path other than said first router, then sending said first data packet to a second router in said least-cost path;
if said first data packet has visited a router in said least-cost path other than said first router, then sending said first data packet to a third router in a first least-delay path from said first router to said destination; and
receiving, at said first router, a second data packet that indicates a path taken by said first data packet to said destination;
wherein said least-cost path differs from said first least-delay path.

8. (Original) The method of Claim 7, further comprising:
receiving, at said second router, said first data packet;
determining whether a second least-delay path from said second router to said destination satisfies a delay requirement indicated by said first data packet;
if said second least-delay path does not satisfy said delay requirement, then performing steps comprising:
updating said first data packet to indicate a wrong way; and
sending said first data packet to said first router.
9. (Original) The method of Claim 8, further comprising:
receiving, at said first router, said first data packet;
determining whether said first data packet indicates a wrong way;
if said first data packet indicates a wrong way, then performing steps comprising:
updating said first data packet to not indicate a wrong way; and
sending said first data packet to said third router.
10. (Currently Amended) A computer-readable storage medium carrying one or more sequences of instructions for discovering a network path that satisfies a quality of service (QoS) requirement, which instructions, when executed by one or more processors, cause the one or more processors to carry out the steps of:
receiving, at a first router, a first data packet that indicates a destination and said QoS requirement;
updating said first data packet to indicate an identity of said first router;
determining whether a least-delay path from said first router to said destination satisfies said QoS requirement;
determining whether said first data packet has visited any router in said least-delay path other than said first router;
if said least-delay path satisfies said QoS requirement and said first data packet has not visited any router in said least-delay path other than said first router, then sending said first data packet to a second router in said least-delay path; and

receiving, at said first router, a second data packet that indicates a path taken by said first data packet to said destination.

11. (Currently Amended) The computer-readable storage medium of Claim 10, wherein said first router has links, and wherein said instructions, when executed by the one or more processors, cause the one or more processors to carry out the steps of:
if said least-delay path does not satisfy said QoS requirement, then performing steps comprising:
determining one or more of said first router's links that satisfy said QoS requirement;
and
sending a copy of said first data packet through said one or more of said first router's links that satisfy said QoS requirement.
12. (Currently Amended) The computer-readable storage medium of Claim 10, wherein said first router has links, and wherein said instructions, when executed by the one or more processors, cause the one or more processors to carry out the steps of:
if said first data packet has visited a router in said least-delay path other than said first router, then performing steps comprising:
determining one or more of said first router's links that satisfy said QoS requirement;
and
sending a copy of said first data packet through said one or more of said first router's links that satisfy said QoS requirement.
13. (Currently Amended) The computer-readable storage medium of Claim 10, wherein said instructions, when executed by the one or more processors, cause the one or more processors to carry out the steps of:
in response to receiving said first data packet, updating a table to indicate that said first router has received a copy of said first data packet.
14. (Original) An apparatus for discovering a network path that satisfies a quality of service (QoS) requirement, comprising:

means for receiving, at a first router, a first data packet that indicates a destination and said QoS requirement;

means for updating said first data packet to indicate an identity of said first router;

means for determining whether a least-delay path from said first router to said destination satisfies said QoS requirement;

means for determining whether said first data packet has visited any router in said least-delay path other than said first router;

means for sending said first data packet to a second router in said least-delay path if said least-delay path satisfies said QoS requirement and said first data packet has not visited any router in said least-delay path other than said first router; and

means for receiving, at said first router, a second data packet that indicates a path taken by said first data packet to said destination.

15. (Original) The apparatus of Claim 14, wherein said first router has links, and further comprising:

means for determining one or more of said first router's links that satisfy said QoS requirement if said least-delay path does not satisfy said QoS requirement; and

means for sending a copy of said first data packet through said one or more of said first router's links that satisfy said QoS requirement if said least-delay path does not satisfy said QoS requirement.

16. (Original) The apparatus of Claim 14, wherein said first router has links, and further comprising:

means for determining one or more of said first router's links that satisfy said QoS requirement if said first data packet has visited a router in said least-delay path other than said first router; and

means for sending a copy of said first data packet through said one or more of said first router's links that satisfy said QoS requirement if said first data packet has visited a router in said least-delay path other than said first router.

17. (Original) The apparatus of Claim 14, further comprising:
means for updating, in response to receiving said first data packet, a table to indicate
that said first router has received a copy of said first data packet.
18. (Original) An apparatus for discovering a network path that satisfies a quality of
service (QoS) requirement, comprising:
a network interface that is coupled to a data network for receiving one or more
packet flows therefrom;
a processor;
one or more stored sequences of instructions which, when executed by the processor,
cause the processor to carry out the steps of:
receiving, at said apparatus, a first data packet that indicates a destination and said
QoS requirement;
updating said first data packet to indicate an identity of said apparatus;
determining whether a least-delay path from said apparatus to said destination
satisfies said QoS requirement;
determining whether said first data packet has visited any router in said least-delay
path other than said apparatus;
if said least-delay path satisfies said QoS requirement and said first data packet has
not visited any router in said least-delay path other than said apparatus, then
sending said first data packet to a router in said least-delay path; and
receiving, at said apparatus, a second data packet that indicates a path taken by said
first data packet to said destination.
19. (Original) The apparatus of Claim 18, wherein said apparatus has links, and wherein
said instructions, when executed by the processor, cause the processor to carry out
the steps of:
if said least-delay path does not satisfy said QoS requirement, then performing steps
comprising:
determining one or more of said apparatus' links that satisfy said QoS requirement;
and

sending a copy of said first data packet through said one or more of said apparatus' links that satisfy said QoS requirement.

20. (Original) The apparatus of Claim 18, wherein said apparatus has links, and wherein said instructions, when executed by the processor, cause the processor to carry out the steps of:
if said first data packet has visited a router in said least-delay path other than said apparatus, then performing steps comprising:
determining one or more of said apparatus' links that satisfy said QoS requirement;
and
sending a copy of said first data packet through said one or more of said apparatus' links that satisfy said QoS requirement.
21. (Original) The apparatus of Claim 18, wherein said instructions, when executed by the processor, cause the processor to carry out the steps of:
in response to receiving said first data packet, updating a table to indicate that said apparatus has received a copy of said first data packet.